

Xerox® PrimeLink® C9065/C9070 Printer



Meet the Xerox® PrimeLink C9065/C9070. Engineered to make a great first impression, these intuitive printers come complete with spot-on color fidelity, best-in-class media latitude and professional finishing capabilities.

SYSTEM SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070	
	COLOR	BLACK-AND-WHITE	COLOR	BLACK-AND-WHITE
8.5 x 11 in. / A4 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 65 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm Up to 30 ppm	Up to 70 ppm Up to 70 ppm Up to 43 ppm Up to 43 ppm Up to 30 ppm	Up to 70 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm Up to 35 ppm	Up to 75 ppm Up to 75 ppm Up to 50 ppm Up to 50 ppm Up to 35 ppm
11 x 17 in. / A3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 32 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm Up to 14 ppm	Up to 35 ppm Up to 35 ppm Up to 21 ppm Up to 21 ppm Up to 14 ppm	Up to 35 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm Up to 17 ppm	Up to 37 ppm Up to 37 ppm Up to 25 ppm Up to 25 ppm Up to 17 ppm
12 x 18 in. / SRA3 60 to 105 gsm uncoated 106 to 176 gsm uncoated 106 to 150 gsm coated 177 to 350 gsm uncoated 151 to 350 coated	Up to 29 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 30 ppm Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm	Up to 30 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm Up to 12 ppm	Up to 33 ppm Up to 33 ppm Up to 19 ppm Up to 19 ppm Up to 12 ppm

Xerox® PrimeLink® C9065/C9070 Printer

AUTO DUPLEX SPEEDS	COLOR	BLACK-AND-WHITE	COLOR	BLACK-AND-WHITE
8.5 x 11 in. / A4 Example: 60 to 105 gsm uncoated	Up to 65 ipm 2-sided 32 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 70 ipm 2-sided 35 sheets per minute	Up to 75 ipm 2-sided 37 sheets per minute
11 x 17 in. / A3 Example: 60 to 105 gsm uncoated	Up to 33 ipm 2-sided 16 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 35 ipm 2-sided 17 sheets per minute	Up to 37 ipm 2-sided 18 sheets per minute
Monthly Duty Cycle	Up to 300,000 pages (maximum volume capacity expected in any one month, not expected to be sustained on a regular basis). ¹			
Average Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month ²			
Technology	Xerox® EA-Eco toner with Ultra Low Melt Technology (2400 x 2400 dots per inch)			
Control Panel Languages	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan			
ACCESSORIES				
Optional	Xerox® EX-c C9065/C9070 Print Server Powered by Fiery® Xerox® EX-i C9065/C9070 Print Server Powered by Fiery® Xerox® EX C9065/C9070 Print Server Powered by Fiery® Simple Catch Tray (Europe only) Offset Catch Tray High Capacity Feeder (A4) 1-Tray Oversized High Capacity Feeder with Storage Cabinet 2-Tray Oversized High Capacity Feeder Interface Decurler Module Xerox® Business Ready Finisher (requires a Vertical Transport Kit) Xerox® Business Ready Finisher Booklet Maker (requires a Vertical Transport Kit) Xerox® Production Ready Finisher (requires Interface Decurler Module) Xerox® Production Ready Booklet Maker Finisher (requires Interface Decurler Module) Xerox® Production Ready Finisher Plus (includes PFIM Partner Finishing Interface Module; requires Interface Decurler Module) XLS Extension Tray Kits Plockmatic Pro50/35™ Booklet Maker Xerox® C/Z Folder Xerox® Basic Punch GBC® AdvancedPunch™ Pro Xerox® Crease/Two-sided Trimmer Xerox® SquareFold® Trimmer Module Xerox® Inserter Convenience Stapler Foreign Device Interface Kit Mobility Plate PostScript Kit VOIP Fax (SW) Kit Fax Kits (1 or 3 Line; requires fax installation kit) Server Fax Kit SIPRNET Kit OHCF Chute MSI Assembly Kit Banner Feed Extension Long USB HUB Kit Smart Card Enablement Kit Integrated RFID Card Reader Kit (external) Xerox® Workplace Suite, Xerox® Workplace Cloud For more information on Xerox® Apps and Solutions, visit www.xerox.com/AppGallery .			

ELECTRICAL REQUIREMENTS			
North America	Voltage: 110-127V Frequency: 50/60 Hz +/- 3%, 20 A		
Europe	Voltage: 220-240V Frequency: 50/60 Hz +/- 3%, 10 A		
Accessories North America: Europe:	Each module requires 120V, 15 A Each module requires 220V, 10 A		
POWER CONSUMPTION			
Running (Average)	PrimeLink C9065: 1,052 watts; PrimeLink C9070: 1,250 watts		
Sleep Mode (Average)	3 watts (Default time to Sleep mode = 1 min.)		
Low Power Mode Recovery Time	Less than 20 seconds		
OPERATING ENVIRONMENT			
Required Temperature Range	50° to 82° F / 10° to 28° C (Relative Humidity less than 62.5% when temp is 32° C or less)		
Required Relative Humidity	15% to 85% (no condensation)		
Sound Power Levels	Operating: 6.8 B(A); Standby: 3.6 B(A)		
Sound Pressure Levels	Operating: 56 dB(A); Standby: 18 dB(A)		
Weight (approximate base unit only)	604 lb., 273 kg		
DIMENSIONS	WIDTH	DEPTH	HEIGHT
Base Unit w/ Offset Catch Tray	62 in. / 1,574 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit w/ Business Ready Finisher	79.1 in. / 2,009 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit w/ Business Ready Booklet Maker Finisher	81.4 in. / 2,068 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit w/ Business Ready Booklet Maker Finisher and C Fold / Z Fold Unit	90.6 in. / 2,301 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit w/ Production Ready Finisher	83.48 in. / 2,120.63 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Base Unit w/ Production Ready Booklet Maker Finisher	94.46 in. / 2,399.43 mm	31.6 in. / 803.5 mm	54.8 in. / 1,391.5 mm
Xerox® Crease/Two-sided Trimmer	23.81 in. / 760.5 mm	28.12 in. / 714.3 mm	39.03 in. / 991.5 mm
Interface Decurler Module	13.38 in. / 340 mm	28.51 in. / 724.3 mm	39.03 in. / 991.5 mm
Xerox® SquareFold® Trimmer	42 in. / 1,066.3 mm	28.5 in. / 724 mm	22 in. / 558.8 mm
High Capacity Feeder	15.3 in. / 389 mm	24.2 in. / 614 mm	14.8 in. / 377 mm

Xerox® PrimeLink® C9065/C9070 Printer

One Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
Two Tray Oversized High Capacity Feeder	38.9 in. / 988 mm	30.0 in. / 762 mm	39.1 in. / 992 mm
CERTIFICATIONS To view the latest list of certifications, go to www.xerox.com/OfficeCertifications .			
Graphic Arts Credentials	FOGRA certification* PANTONE® Matching System* PANTONE GOE* PANTONE PLUS* Adobe® PDF Print Engine* Adobe® PostScript® 3™ (certified) IDEAlliance Digital Press Certified to GRACoL® specifications *requires an additional Print Server option		
PAPER HANDLING			
SINGLE-PASS DUPLEX AUTOMATIC DOCUMENT FEEDER (DADF) - NETWORK SCANNING			
Capacity³	250 sheets of plain paper – 20 lb. / 75 gsm		
Speed	Up to 270 ipm color / 270 ipm black-and-white (2-sided, 8.5 x 11 in. / A4)		
Paper Sizes	Custom sizes: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3		
Weights	16 to 53 lb. bond / 38 to 200 gsm		
TRAY 5 (BYPASS)			
Capacity³	Up to 250 sheets		
Sizes	Custom sizes: 4 x 6 in. to 13 x 19 in. / 100 x 148 mm to 330.2 x 482.6 mm (A5 to SRA3) XLS sheet size: 13 x 26 in. (330 x 660 mm)		
Weights	16 lb. bond to 130 lb. cover / 60 to 350 gsm (60 to 350 gsm uncoated; 106 to 350 gsm coated); XLS sheet: 60-220 gsm		
Envelope Capacity	30 to 50 envelopes		
Envelope Sizes	#10 Commercial, Monarch (including custom size), C4, C5 (Available as Tray 5 (Bypass). Paper Size Default within tools. Run flap open at the trail edge). Custom sizes: 7.5 x 6.7 in. to 9.45 x 6.81 in./ 190 x 170 mm to 240 x 173 mm Digital Laser envelopes recommended.		
Envelope Weights	75 to 90 gsm		
TRAYS 1 TO 4			
Capacity³	Tray 1: 500 sheets Tray 2: 500 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets		
Sizes	Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to SRA3 Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / A5 to A3 Tray 3: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4 Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4		
Weights	Trays 1 and 2: 16 lb. bond to 96 lb. cover / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated) Trays 3 and 4: 16 lb. bond to 96 lb. cover / 60 to 256 gsm (60 to 256 gsm uncoated; 106 to 220 gsm coated)		
OPTIONAL HIGH CAPACITY FEEDER (HCF)			
Capacity³	2,000 sheets		

Sizes	7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4)
Weights	16 lb. bond to 60 lb. cover / 60 to 350 gsm (uncoated and coated)
OPTIONAL OVERSIZED HIGH CAPACITY FEEDER (OHCF) – 1 OR 2 TRAY OPTIONS	
Capacity³	1 Tray OHCF: 2,000 sheets plus Storage Cabinet 2 Tray OHCF: 4,000 sheets
Sizes	1 Tray OHCF: 7.2 x 10 in. / 182 x 250 mm (B5) to 13 x 26in. / 330x660 mm 2 Tray OHCF: 4 x 6 in. / 102 x 152 mm to 13 x 26in. / 330x660 mm
Weights	16 lb. bond to 110 lb. cover / 60 to 350 gsm (uncoated and coated); XLS sheet: 60-220 gsm
TOTAL CAPACITY	
Standard Capacity	3,250 sheets (includes Tray 5 (Bypass) and Trays 1-4)
Maximum Capacity	7,250 sheets (includes Tray 5 (Bypass), Trays 1-4 and Two-tray Oversized High Capacity Feeder)
Automatic Two-Sided	94 lb. cover / 256 gsm auto duplex 130 lb. cover / 350 gsm manual duplex for all stocks from Tray 5 (Bypass) and optional Oversized High Capacity Feeder
FINISHING	
OFFSET CATCH TRAY	
Capacity³	Up to 500-sheet stacking
Simple Catch Tray (Europe only)	Up to 500-sheet stacking
OPTIONAL BUSINESS READY FINISHER	
Capacity³	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11 x 17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 60 to 350gsm (coated and uncoated) Top Tray 16 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb./90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
OPTIONAL BUSINESS READY BOOKLET MAKER FINISHER	
Capacity³	Offsetting Top Tray: 500 sheets of 8.5 x 11 in. / A4 unstapled Stacking Stapling Tray: 1,500 sheets of 8.5 x 11 in. / 11 x 17 in. / A4 / A3 / SRA3 unstapled or 200 stapled sets of 8.5 x 11 in. / A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of 11 x 17 in. / A3 / SRA3
Sizes	4 x 6 in. to 12 x 19 in. / A6 to SRA3 for stacking 7.25 x 10.5 in. to 11 x 17 in. / B5 to A3 for stapling 5.5 x 8.5 in. / A5 output to top tray; punch and offset
Weights	16 lb. bond to 110 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 16 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray 16 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Booklet Maker

Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 24 lb/90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported
Hole Punch North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Booklet Maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated), Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4, 12 x 18 in., SRA3 supported
OPTIONAL C/Z FOLDER UNIT	
Types	C Fold, Z Fold and Z Half Fold
Capacity³	40 sheets
Sizes	C Fold and Z Fold: Letter – 8.5 x 11 in. / A4 SEF only Z Half Fold: Tabloid – 11 x 17 in. / A3 only
Weights	16 to 24 lb. bond / 64 to 90 gsm
Output Tray	Envelope Tray: C Fold, Z Fold and Tri-fold Stacker Tray or Top Tray: Z Half Fold
OPTIONAL PRODUCTION READY FINISHER (REQUIRES INTERFACE DECURLER MODULE)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 3,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 18 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray
Multiposition Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	2-3 Hole Punch 2-4 Hole Punch 4 Hole Swedish Punch (Optional)
Inserting Capacity Capacity: Sizes: Weights:	250 sheets of 350 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. / A3, A4, B4, B5 18 lb. bond to 130 lb. cover / 64 to 350 gsm
Decurling	Included with Interface Decurler Module and Standard Finisher Bidirectional with Auto and Manual settings
OPTIONAL PRODUCTION READY FINISHER PLUS (REQUIRES INTERFACE DECURLER MODULE)	
	Provides same function as the Production Ready Finisher with a 500-sheet top tray and 2,000-sheet stacker tray. Used to connect third-party inline finishing options. Includes PFIM Partner Finishing Interface Module.
OPTIONAL PRODUCTION READY FINISHER WITH BOOKLET MAKER (REQUIRES INTERFACE DECURLER MODULE)	
Capacity	Top Tray: 500 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4 Lower Tray: 2,000 sheets of 20 lb. bond / 80 gsm, 8.5 x 11 in. / A4
Sizes	4 x 6 in. to 13 x 19 in. / A6 to SRA3
Weights	18 lb. bond to 110 lb. cover / 60 to 350 gsm (coated and uncoated) Top Tray 18 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Stacker Tray 18 lb. bond to 110 lb. cover / 60 to 256 gsm (coated and uncoated) Booklet Maker
Multi-position Stapling	Up to 100 sheets of 20 lb. bond / 80 gsm
Hole-punching North America: Europe:	2-3 Hole Punch (Optional) 2-4 Hole Punch (Optional) 4 Hole Swedish Punch (Optional)

Xerox® PrimeLink® C9065/C9070 Printer

Inserting Capacity Capacity: Sizes: Weights:	250 sheets of 350 gsm 5.5 x 8.5 in., 8 x 10 in., 8.5 x 11 in., 8.5 x 14 in., 8.5 x 12.5 in., 11 x 15 in., 11 x 17 in. A3, A4, B4, B5 18 lb. bond to 130 lb. cover / 64 to 350 gsm
Decurling	Included with Interface Module and Standard Finisher Bidirectional with Auto and Manual settings
Booklet Making Capacity	Saddle-stitch 2 to 30 sheets of 79 gsm (uncoated) or 2 to 25 sheets (coated); Bi-fold up to 5 sheets 8.5 x 11 in., 8.5 x 13 in., 8.5 x 14 in., 9 x 11 in., 11 x 15 in., 11 x 17 in., 12 x 18 in., 13 x 18 in. / A4, B4, A3, SRA3
OPTIONAL XEROX® CREASE AND TWO-SIDED TRIMMER	
Trim Sheet Sizes	7.7" x 8.3" (194 mm x 210 mm) to 13.0" x 19.21" (330.2 mm x 488 mm)
Trim Booklet Sizes	7.17" x 10.1" (182 mm x 257 mm) to 13.0" x 19.21" (330.2 mm x 488 mm)
Crease Weights	106-350 gsm (72 lb. text to 129 lb. cover) coated
Weights	60-350 gsm (uncoated) and 106-350 gsm (coated)
OPTIONAL GBC® ADVANCEDPUNCH PRO	
Punch Configuration Sizes	5.5 x 8.5 in. / 148 x 210 mm (A5) LEF to 13 x 19.2 in. / 330 x 488 mm (SRA3) SEF
Weights	20 lb. bond to 110 lb. cover / 75 to 300 gsm (uncoated); 28 lb. bond to 110 lb. cover / 106 to 300 gsm (coated)
Dies	Wide selection of slide-in / slide-out GBC punch die sets available
OPTIONAL XEROX® SQUAREFOLD® TRIMMER MODULE	
Capacity	5 to 20-sheet booklets (up to 80 imaged sides) at 24 lb. / 90 gsm 5 to 25-sheet booklets (up to 100 imaged sides) at 20 lb. / 80 gsm
Sizes	Custom sizes: 8.5 x 11 in. to 13 x 18 in. / A4 to SRA3
Weights	18 lb. bond to 110 lb. cover / 64 to 350 gsm
OPTIONAL CONVENIENCE STAPLER	
Capacity	50 sheets (24 lb. / 90 gsm media)
PRINT	
Print Resolution	Up to 2400 x 2400 dpi
Line Screens	600, 300, 200 and 150 Clustered Dot, 200 Rotated Line Screen (depending on print server / controller selected)
Registration	<ul style="list-style-type: none"> Advanced registration technology for tighter control Simple Image Quality Adjustment (SIQA) for de-skew, registration and density uniformity (Available on all configurations as a Maintenance Tool: Alignment Adjustment) +/-1.2 mm front to back registration Internal Trays
First-Print-Out Time	PS-A4 LEF Simplex Color 10.4 seconds / Black-and-white 8.5 seconds
Print Features	<ul style="list-style-type: none"> Print, copy, fax and scan, including scan to PC, USB or email, and mobile printing Benchmark image quality with 2400 x 2400 dpi resolution and EA low melt EA-Eco toner for a smooth finish Makes mobile printing simpler and more convenient Expansive media range lets you print everything from postcards to posters, both coated and uncoated stock, up to 350 gsm Xerox Extensible Interface Platform® (EIP 3.7.3) allows you to connect to third-party software solutions that you can access from the touch-screen of the device or on your own mobile device. Your choice of servers to best fit your environment: <ul style="list-style-type: none"> Xerox® Integrated Color Server for the Xerox® PrimeLink C9065/C9070 Printer Xerox® EX-c PrimeLink C9065/C9070 Print Server Powered by Fiery®

Xerox® PrimeLink® C9065/C9070 Printer

	<ul style="list-style-type: none"> - Xerox® EX-i PrimeLink C9065/C9070 Print Server Powered by Fiery - Xerox® EX PrimeLink C9065/C9070 Print Server Powered by Fiery <p>Inline finishing options offer a professional polish with banner printing, stapling, hole-punching, folding and booklet making for presentations, brochures, reports and newsletters.</p> <p>Be secure with integrated security features such as IP filtering, image overwrite, secure print, encrypted Scan to Email, authentication and IPv6 support.</p>
Print Drivers	Xerox® Smart Start Driver Installer, Xerox® Global Print Driver® (v3, v4)
PRINT SOLUTIONS	
Mobile Printing (optional)	Apple® AirPrint®, Google Cloud Print™ Ready, Mopria® Print Service Plug-in for Android, Wi-Fi Direct Printing, Xerox® @PrintByXerox App, See more at www.xerox.com/MobileSolutions ; Xerox® Workplace Cloud/Suite Mobile Print Solution. Learn more at www.xerox.com/MobilePrintApp .
Xerox Apps	<ul style="list-style-type: none"> • On Box Apps include Xerox® @printbyXerox App for mobile printing and Xerox App Gallery to download a multitude of Print Management Apps.
COPY	
First-Copy-Out Time From the Platen: From the DADF:	As fast as 7.8 seconds color / 5.1 seconds black-and-white As fast as 9.6 seconds color / 5.3 seconds black-and-white
Warm Up Time	90 seconds (from cold powered down to Ready Copy)
Digital Imaging	<p>Auto color Auto rotation Image shift Edge erase Auto centering Original type selection (photo and text, photo, text, map) Includes subtypes lighter/darker Background suppression Auto and manual contrast Sharpness Color balance, color shift and saturation</p>
Reduce / Enlarge	<p>Variable zoom from 25% to 400% in 1% increments Anamorphic zoom Six user-programmable percentages</p>
Special Features	<p>Auto paper select Auto reduction/enlargement to fit selected paper size Auto tray switching Automatic job recovery Auto color selection Area designation Poster mode Annotation Single/Dual color Booklet creation Multi-up – 2, 4 or 8 up Repeat image Negative image Mirror image Covers insertion (front only, front and back, back only, blank or printed) Build job (enables special programming for different pages in one document – can be used for inserts, different paper sources and mixing input from the document glass and the document feeder) Job interrupt Book copying Sample job Mixed-size originals</p>

Xerox® PrimeLink® C9065/C9070 Printer

	<p>Sheet insert Stamping/Bates 2-in-1 X Y zoom Zoom range 25 to 400 % Margin shift Photo Mode Poster Mode Preset Reduce / Enlarge Program ahead Covers Erase, Image Repeat, Image Rotate Interrupt</p>
SCAN	
Concurrency	Scan while printing or while it is transferring scan to network or fax jobs
Scan Features	<p>Mixed size originals Edge erase Reduction/enlargement Fit to size Scan build job Compression Quality / File Size Control Original type (photo and text, photo, text) Auto background and shadow suppression Job flow sheets Scan to USB Preview scan job</p>
INPUT SPEED	
Resolution	<p>600 x 600 dpi 400 x 400 dpi 300 x 300 dpi 200 x 200 dpi</p>
Maximum Scan Area	Originals up to 11 x 17 in. / A3
Network Print Services	<p>Port 9100 RFC 1179 (LPR) Print to Mailbox and Release</p>
File Formats	<p>PDF Image Only PDF Searchable PDF (Linearized) PDF (A-1 Level A) TIFF V6 JFIF XPS</p>
Document Management Fields (Metadata)	<p>One to six user-programmable metadata fields per scan job Customized fields viewed on user interface Variable data entered using virtual keyboard</p>
Scan Features	<p>Scan to Home Scan to Desktop WIA Scan to Desktop TWAIN Scan to Mailbox Scan to FTP Scan to sFTP (via EIP solution) Scan via SMB Scan via HTTP</p>

	<p>Scan via HTTPS Scan to USB Storage Device Scan to Fax Server Scan to Multiple Destinations Scan to Microsoft Network Folder</p>
Supported Scan Destinations (Standard)	<p>Scan to Email, Scan to Folder, to PC, to Mailbox (private and public), Scan to USB, FTP, SMB, Desk, Text searchable PDF, PDF/A, XPS, Thumbnail Preview</p>
Scan to Email Features	<p>Color scanning, Auto Color, Grayscale, Black-and-white Direct document email from device Manual or directory Exchange / Notes / LDAP address searching Signing and encryption Email over SSL Preview scan job</p>
Authentication	<p>SMTP authentication, POP before SMTP, System credentials Single sign on (LDAP, SMB, Kerberos authentication) Scanning Security-TLS</p>
FAX (OPTIONAL) – ONE OR THREE LINE FAX OPTIONS	
Maximum Scan Area	<p>11 x 17 in. SEF</p>
Fax Send Features	<p>iFax Lan Fax IP Fax (optional) Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>
Fax Print Features	<p>Print from USB Storage Device Media Print Unicode Printing</p>
Fax Features	<p>iFax Lan Fax IP Fax (optional) Fax Forward to Email Fax Forward to FTP destination Fax Forward to SMB destination Fax Forward to Fax destination</p>
DEVICE MANAGEMENT	
XEROX® CENTREWARE® INTERNET SERVICES – INTEGRATED WEB PAGES PROVIDED BY THE DEVICE	
Device Status	<p>Web server embedded in Network Controller:</p> <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts
Job Submission	<p>Print ready files: PS, PCL, TIFF, PDF, JPG, XPS Output feature selection (2-sided, output color, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)</p>
Device Administration	<p>Allows simple, remote installation setting of configuration options and management of the device</p>
Browsers	<p>Internet Explorer Safari Mozilla Firefox Opera Chrome</p>
Support	<p>Install print/scan drivers and online support available via web page</p>

Xerox® PrimeLink® C9065/C9070 Printer

Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese	
REMOTE SERVICES		
Automated Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.	
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.	
SECURITY		
Features	<ul style="list-style-type: none"> Access Controls AES 256-bit Encryption Audit Log Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite IP Address Filtering IPsec Network Authentication Pre-installed Self-Signed Certificates Role Based Permissions Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL (TLS 1.0, 1.1, 1.2) SIPRnet 	
PRINT SERVER		
XEROX® INTEGRATED COLOR SERVER		
Processor	1.6 GHz Dual-core	
Memory	4 GB system plus 1 GB page memory	
System Disk	320 GB Hard Disk Drive	
Display	10.4 in. color touchscreen flat-panel	
Device Operating System	Linux	
PDLs Page Description Languages	Adobe® PostScript® 3™ PDF PCL® 5c, 6 XML Paper Specification (XPS®) (optional)	
Operating Systems	Windows® XP Windows Server 2003 (32- and 64-bit) Windows Server 2008 (32- and 64-bit) Windows Server 2012 Windows Vista (32- and 64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Mac OS® 10.7 and above	Solaris® 9, 10 HP-UX® 11 v2 IBM® AIX® 5 Red Hat® Fecora® Core 15-17 Red Hat Enterprise 4 and 5 openSUSE® 11 and 12 Ubuntu® Unix®
Print Drivers Supported	Please refer to www.xerox.com/support for specifics. As new operating system versions are added, support is also added for the Xerox® PrimeLink C9065/C9070 Printer. Also note that there is more than one print driver based on the configuration purchased (e.g., digital front ends, Xerox® Global Print Driver)	

Xerox® PrimeLink® C9065/C9070 Printer

	<p>Windows 7, 32-bit Windows 7, 64-bit Windows 8, 32-bit Windows 8, 64-bit Windows 8.1 Update 1, 32-bit Windows 8.1 Update 1, 64-bit Windows 10, 32-bit Windows 10, 64-bit Windows 10S, 32 bit & 64-bit Windows Server 2008, 32-bit (SP2) Windows Server 2008, 64-bit (SP2) Windows Server 2008 R2, 64-bit (SP1) Windows Server 2012, 64-bit Windows Server 2012 R2, 64-bit Windows Server 2016, 64-bit Windows Server 2019, 64-bit Citrix® Xen App 7.15 Citrix® Xen Desktop 7.15 Citrix® Virtual Apps and Desktops 7 Novell Open Enterprise Server 2018 Cluster: Windows Server 2008 32- and 64-bit, 2008 R2, 64-bit; Windows Server 2012 64-bit; Windows 2012 R2 64-bit, Windows Server 2016 & 2019, 64 macOS High Sierra (10.13) macOS Mojave (10.14) macOS Catalina (10.15) Fedora Core 29 x32 Fedora Core 29 x64 Fedora Core 30 x32 Fedora Core 30 x64 Ubuntu 18.04 x32 & x64 Ubuntu 19.04 x64 OpenSuse 15.0 x32 & x64 Solaris 11.4 x86 Solaris SPARC 11.4 Power PC AIX 7.2 Itanium HP-UX 11i v3 Update 18 Xerox® Global Print Driver® v3 & v4</p>
<p>Features</p>	<p>Automatic two-sided Bi-directional print drivers provide device and job status Custom Macintosh Driver (Watermark, Booklet Creation, JBA, Secure, Sample, Delay Print) Secure print Delay print Embedded web server for remote control/monitor/setup Enhanced gloss Sample set Booklet creation Cover selection Paper selection by attribute N-up Watermarks Banner sheets Banner printing Fit to new paper size Output tray selection Print calibration (with EFI) Print from USB (No Print Driver required)</p>
<p>Connectivity</p>	<p>Ethernet interface (10 MBTX / sec, 100 MBTX / sec, 1000 MBTX / sec)</p>

ADDITIONAL PRINT SERVER OPTIONS	
XEROX® EX-C C9065/C9070 PRINT SERVER POWERED BY FIERY®	
Processor	AMD® GX-424CC processor 2.4 GHz
Memory	2 GB RAM
Hard Drive	500 GB
Server Operating System	Linux®
Print Languages (PDL)	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and MicroSoft® native formats via Fiery® Hot Folders
Features	<p>Easy-to-use color adjustment tools that deliver outstanding color quality from all applications and file formats.</p> <ul style="list-style-type: none"> • Print logo and corporate colors correctly (including PANTONE colors) • Print high-quality photos and images • Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost effectively in-house • Easily print files with mixed paper sizes and types • Fully integrated with Xerox® ConnectKey® Apps • Paper Catalog • Command WorkStation • Fiery Freeform • Fiery Remote Scan
Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
Additional Options	<ul style="list-style-type: none"> • Options Bundle <ul style="list-style-type: none"> – Fiery Spot-On™ with PANTONE approved libraries – Fiery Hot Folders – Fiery Virtual Printers – Auto Trapping • Color Profiler Suite (with ES2000) • Network Hub Kit • Spot On • Hot Folders/ Virtual Printers
XEROX® EX-I C9065/C9070 PRINT SERVER POWERED BY FIERY®	
Processor	Intel 3-6100 (3.7 GHz) Processor (Performance optimized by proprietary combination of EFI Technology, VX600 ASIC and software)
Memory	4 GB
Hard Drive	500 GB
Server Operating System	Linux®
Print Languages (PDL)	Adobe PostScript® Level 1,2,3, Adobe PDF, EPS, PCL® 6C, TIFF, JPG, and MicroSoft® native formats via Fiery® Hot Folders
Features	<ul style="list-style-type: none"> • Productivity starts with a fast RIP. The Integrated Fiery Color Server enables you to print large and/or complex Microsoft® Office® documents, PowerPoint® files and color-critical PDFs accurately and quickly. • Fully integrated with Xerox® ConnectKey® Apps. • Simplify and streamline your workflow. Automate job submission of repetitive job types to achieve productive, error-free workflows with Hot Folders and Virtual Printers. • Take advantage of commonly used Fiery presets to save time when submitting jobs. With Fiery server technology, even novice users can perform complex jobs using the pre-set drivers configured for the task. • Get the color right. Produce precise, exact color from all applications, platforms and formats with Fiery color management tools. • Turn up the impact with variable information. Customize your output to a specific audience with varying text, photos and graphics with the Integrated Fiery Color Server’s basic variable data printing capabilities.

Xerox® PrimeLink® C9065/C9070 Printer

	<ul style="list-style-type: none"> • Print high-quality photos and images • Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost effectively in-house • Easily print files with mixed paper sizes and types • Command WorkStation • Fiery JDF • Secure Erase • Paper Catalog • Fiery Compose • Fiery Remote Scan
Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100
Additional Options	<ul style="list-style-type: none"> • Productivity Package <ul style="list-style-type: none"> – Fiery ImageViewer – Fiery Image Enhance Visual Editor – Control Bar Builder – Postflight Report – Configurable Auto Trapping – Paper Simulation – Graphic Arts Filters for Hot Folders – Rush Print, Schedule Print and Print/Process Next – Fiery JobFlow Base • Fiery impose • Color Profiler Suite (with ES2000) • Network Hub Kit
	For more information, go to www.xerox.com
XEROX® EX C9065/C9070 PRINT SERVER POWERED BY FIERY®	
Processor	Intel® Core™ i5-6500 Processor (3.2 up to 3.6 GHz with Turbo), Quad Core
Memory	8 GB
Hard Drive	1 TB
Server Operating System	Windows 10
Print Languages (PDL)	Adobe PostScript® Level 3, Adobe PDF, EPS, PCL® 6C, PCL 5, TIFF, JPG, MicroSoft® native formats via Fiery® Hot Folders and Adobe PDF Print Engine (APPE)
Features	<ul style="list-style-type: none"> • Job-based Calibration Integration <ul style="list-style-type: none"> – Fiery Spot-On finds the best match of PANTONE®, PANTONE Series, RGB, CMYK, L*a*b* and Spot Colors – Color Modes for professional proofing and enhanced production color requirements – Maximum print density • Fully integrated with Xerox ConnectKey® Apps. • Fiery technology increases your profits by delivering high-impact documents with vibrant images and color that exceed your customers’ expectations and also meets tight turnaround times and allows you to do more work by automating manual tasks and removing bottlenecks that slow down production. • The Fiery Command WorkStation increases your production and reduces errors and waste by centralizing job management via its intuitive user interface. Simplify your labor-intensive document composition and imposition tasks even more by using Fiery SeeQuence Impose and Compose’s intuitive interface. • Print high-quality photos and images • Use Fiery VUE, the “visual print driver,” to create and print professional booklets quickly, easily and cost effectively in-house • Easily print files with mixed paper sizes and types • Paper Catalog • Sequential Printing • Fiery JDF • Insert Tabs

Xerox® PrimeLink® C9065/C9070 Printer

Connectivity	Direct Connection (Single IP) & Optional Network Switch (Dual IP): TCP/IP, AppleTalk, SNMP, IPv4, IPv6, IPP, FTP, SMB, WSD, Bonjour, Port 9100		
Additional Options	<ul style="list-style-type: none"> • Fiery Graphic Arts Package, Premium Edition (optional) provides expert tools for preflighting and troubleshooting jobs • Fiery Color Profiler Suite (optional) creates, verifies and edits color profiles with a single profiling solution • Furniture Kit – Monitor, Keyboard, and Mouse • Color Profiler Suite (with ES2000) • Removable HDD • Network Hub Kit 		
	For more information, go to www.xerox.com		
SUPPLIES		YIELD	PART NUMBER
Toner Cartridges (Metered)	Black	30,000 pages ⁴	006R01521
	Cyan	34,000 pages ⁴	006R01524
	Magenta	32,000 pages ⁴	006R01523
	Yellow	34,000 pages ⁴	006R01522
Toner Cartridges (Sold)	Black	30,000 pages ⁴	006R01734 (NASG,ESG) 006R01738 (DMO)
	Cyan	34,000 pages ⁴	006R01737 (NASG, ESG) 006R01741 (DMO)
	Magenta	32,000 pages ⁴	006R01736 (NASG, ESG) 006R01740 (DMO)
	Yellow	34,000 pages ⁴	006R01735 (NASG, ESG) 006R01739 (DMO)
Black Drum Cartridge	1 Cartridge	190,000 pages ⁴	013R00663
Color Drum Cartridge	1 Cartridge per Color	85,000 pages ⁴	013R00664
Charge Corotron	For Black Drum	190,000 pages ⁴	013R00650
Fuser	110V	200,000 pages ⁴	008R13102
	220V	200,000 pages ⁴	008R13065
Waste Toner Container	1 Cartridge	50,000 pages ⁴	008R12990
Feed Roll Kits	1 Assembly	300,000 pages ⁴	008R13169

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Expected regular monthly throughput.

³ Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

⁴ Approximate pages. Declared Yield based on 5 page job size, 30% color and 70% black-and-white ratio, using letter / A4 media. Yield will vary based on media size, image area coverage, job run length, media orientation and usage patterns.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit www.xerox.com/About-Xerox/Recycling.

Learn more at www.xerox.com/PrimeLink

