

# Xerox® VersaLink® B610 Printer



VersaLink B610 Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.ConnectKey.com](http://www.ConnectKey.com).

SYSTEM SPECIFICATIONS	VERSALINK B610
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 65 ppm black-and-white Up to 63 ppm black-and-white Up to 54 ppm black-and-white
<b>Two-sided Speed<sup>1</sup></b> 8.5 x 11 in. A4 / 210 x 297 mm 8.5 x 14 in. / 216 x 356 mm	Up to 58.5 ppm black-and-white Up to 56 ppm black-and-white Up to 30.1 ppm black-and-white
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 300,000 pages / month
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 30,000 pages
<b>Hard Drive</b>	Optional 320 GB HDD
<b>Processor</b>	1.05 GHz ARM Dual Core
<b>Memory</b>	2 GB
<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair
<b>Controller Features</b>	Configuration Cloning, Xerox Extensible Interface Platform®, Xerox® App Gallery App, Xerox® Standard Accounting Tool, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian

DEVICE SPECIFICATIONS				
ELECTRICAL REQUIREMENTS				
<b>North America</b>	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 12 A			
<b>Europe and Other Geographies</b>	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3% Hz, 8 A			
POWER CONSUMPTION				
<b>Continuous Print<sup>4</sup></b>	Maximum: 900 watts or less			
<b>Ready (Standby)<sup>4</sup></b>	72 watts or less			
<b>Energy Saver (Sleep Mode)<sup>4</sup></b>	0.79 watts or less			
<b>Power Off Mode<sup>4</sup></b>	220-240 VAC: 0.3 watts or less 110-127 VAC: 0.2 watts or less			
OPERATING ENVIRONMENT				
<b>Required Temperature Range (Storage)</b>	32° to 95° F / 0° to 35° C			
<b>Required Temperature Range (Operating)</b>	50 to 90° F / 10 to 32° C			
<b>Required Relative Humidity</b>	15% to 85%			
<b>Sound Power Levels</b> Running Standby	70 dB(a) or less 42 dB(a) or less			
<b>Sound Pressure Levels</b> Running Standby	56.8 dB(a) or less 27.1 dB(a) or less			
<b>Boot Time (from Off to UI Ready)</b>	Less than 79 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	Less than 47 seconds			
DIMENSIONS AND WEIGHT (UNPACKAGED)	WIDTH	DEPTH	HEIGHT	WEIGHT
<b>Base Unit</b>	16.8 in. / 427.4 mm	18.3 in. / 465.5 mm	17.5 in. / 443.4 mm	49.2 lb. / 22.3 kg
<b>Base Unit with Additional 550-sheet Tray</b>	16.8 in. / 427.4 mm	18.3 in. / 465.5 mm	22.3 in. / 566.4 mm	63.8 lb. / 28.9 kg
<b>Base Unit with High Capacity Feeder</b>	16.8 in. / 427.4 mm	18.3 in. / 465.5 mm	35.5 in. / 902.4 mm	92.5 lb. / 42 kg
<b>Base Unit with High Capacity Feeder and Finisher</b>	16.8 in. / 427.4 mm	18.3 in. / 465.5 mm	45.3 in. / 1150.4 mm	107.5 lb. / 48.8 kg
<b>Base Unit with High Capacity Feeder and Mailbox</b>	16.8 in. / 427.4 mm	18.3 in. / 465.5 mm	45.3 in. / 1150.4 mm	104.2 lb. / 47.3 kg
<b>550-sheet Tray</b>	16.5 in. / 420 mm	10.4 in. / 464.5 mm	4.8 in. / 123 mm	14.6 lb. / 6.6 kg
<b>High Capacity Feeder (includes Caster Base)</b>	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	18 in. / 459 mm	43.3 lb. / 19.7 kg
<b>Cabinet (includes Caster Base)</b>	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	13.2 in. / 336 mm	37 lb. / 16.6 kg
<b>Caster Base</b>	28.5 in. / 724.2 mm	30.4 in. / 772.1 mm	3.5 in. / 90 mm	18.7 lb. / 8.5 kg
<b>Mailbox</b>	17.7 in. / 450.8 mm	18.8 in. / 477.6 mm	9.8 in. / 248.0 mm	11.7 lb. / 5.3 kg

Xerox® VersaLink® B610 Printer

<b>Finisher</b>	17.7 in. / 450.8 mm	16.2 in. / 411.0 mm	9.8 in. / 248.0 mm	15 lb. / 6.8 kg
<b>DIMENSIONS AND WEIGHT (PACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
<b>Base Unit</b>	22.8 in / 580 mm	25 in / 634 mm	23.9 in / 607 mm	61.6 lb. / 28 kg
<b>550-sheet Tray</b>	21 in / 535 mm	23 in / 584 mm	9.8 in / 248 mm	18.7 lb. / 8.5 kg
<b>High Capacity Feeder (includes Caster Base)</b>	22.4 in / 568 mm	26.1 in / 663 mm	28 in / 711 mm	79.4 lb. / 38 kg
<b>Cabinet (includes Caster Base)</b>	23 in / 584 mm	24.8 in / 629 mm	23.5 in / 597 mm	57.3 lb. / 28 kg
<b>Caster Base</b>	23 in / 585 mm	24.4 in / 619 mm	13 in / 330 mm	39.7 lb. / 18 kg
<b>Mailbox</b>	22.6 in / 573 mm	20.4 in / 518 mm	15.2 in / 386 mm	16.3 lb. / 7.8 kg
<b>Finisher</b>	22.6 in / 573 mm	15.7 in / 398 mm	15.2 in / 386 mm	18.6 lb. / 8.8 kg
<b>Wireless Network Adapter (Wi-Fi Kit)</b>	7.4 in / 188 mm	5.4 in / 136 mm	2.2 in / 55 mm	1.05 lb. / 0.1 kg
<b>Hard Drive</b>	4.5 in / 116 mm	1.8 in / 46 mm	7 in / 178 mm	0.4 lb. / 0.18 kg
<b>CERTIFICATIONS</b>				
To view the latest list of certifications, go to <a href="http://www.xerox.com/OfficeCertifications">www.xerox.com/OfficeCertifications</a> .				
<b>PRINT</b>				
<b>First-Print-Out Time</b>	As fast as 3.7 seconds			
<b>Print Resolution</b>	Up to 1200 x 1200 dpi			
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™			
<b>Maximum Print Area</b>	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper			

<p><b>Print Features</b></p>	<p>Application Defaults            Banner Pages Enable/Disable            Bi-directional Real-time Status            Booklet Layout            Draft Mode            Fit to New Paper Size            Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)            Job Monitoring (Client or Local User Interface)            N-up Page Layout (up to 16 pages per sheet)            Paper Selection by Attribute            Personal Print            Print Around Enable / Disable            Print from USB            Sample Set            Saved Job            Scaling            Secure Print            Skip Blank Pages            Special Pages (exception page programming: covers, inserts, exceptions pages)            Store and Recall Driver Settings            Stored Jobs            Deletion Two-sided            Printing            Watermark (predefined and custom)            Earth Smart Driver Settings</p>
<p><b>Print from USB</b></p>	<p>Allows walk-up printing from Type A USB port            Supports direct printing from computer via Type B USB port            Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</p>
<p><b>Operating Systems</b></p>	<p>Windows® 7, 8, 8.1, 10            Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016            macOS® 10.11, 10.12, 10.13            Citrix®            Redhat® Enterprise Linux®            Fedora Core            IBM® AIX®            HP-UX®            Oracle® Solaris            SUSE®            SAP®</p> <p>Note: For information about supported versions for the above operating systems, please visit our Drivers &amp; Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a></p>
<p><b>Fonts</b></p>	<p>PostScript fonts: 136            PCL fonts: 83</p>
<p><b>Xerox® Global Print Driver®</b></p>	<p>A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.</p>
<p><b>Xerox® Pull Print Driver</b></p>	<p>Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.</p>

SOFTWARE SOLUTIONS	
<b>Xerox® ConnectKey Apps (Found at the Xerox App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey Apps to the ConnectKey Technology-enabled device.
MOBILE SOLUTIONS AND MOBILE DEVICE APPS	
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Google Cloud Print™</b>	Google Cloud Print connects print devices to the web, enabling users to print the applications they use every day from smartphones, tablets, Chromebook™ notebook computers and any other web-connected device.
<b>Mopria® Certified</b>	ConnectKey Technology-enabled print devices are Mopria certified. Mopria certification ensures you can print wirelessly from your Mopria supported (Android) smart phone, tablet and other mobile devices instantly and easily.
<b>Xerox® @printbyXerox App</b>	@printbyXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
<b>Xerox® Print Services plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Services plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.
SECURITY	
<b>Security Features</b>	<ul style="list-style-type: none"> <li>Access Controls</li> <li>AES 256-bit Encryption</li> <li>Audit Log</li> <li>Certificate Path Validation</li> <li>Certificate Revocation List (CRL) / Status Protocol</li> <li>(OCSP) Detection of External Program Falsification (XCP</li> <li>Plug-in) Cisco® Identity Services Engine (ISE) Integration</li> <li>Domain Filtering</li> <li>FIPS 140-2</li> <li>Firmware Verification</li> <li>Immediate Disk Overwrite*</li> <li>IP Address Filtering</li> <li>IPsec</li> <li>Network Authentication</li> <li>Port Filtering</li> <li>Pre-installed Self-Signed Certificates</li> <li>Role Based Permissions</li> <li>Secure Print</li> <li>Security Certificate Management</li> <li>Smart Card Enablement (CAC/PIV/.NET)</li> <li>SNMPv3</li> <li>Status Protocol (OCSP)</li> <li>TLS/SSL</li> <li>Trusted Platform Module (TPM)</li> </ul> <p>*Requires HDD/Productivity Kit</p>

ACCOUNTING	
<b>XEROX® STANDARD ACCOUNTING / NETWORK ACCOUNTING (STANDARD)</b>	
<b>Tracking</b>	Print usage
<b>Accounting</b>	<p>Xerox® Standard Accounting Tool                      Up to 1,000 User Accounts without HDD                      Up to 9,999 User Accounts with HDD                      Up to 500 General Accounts</p> <p>Network Accounting (Job Based Accounting)                      Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD                      Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD                      Up to 14,000 Accounting Records (transactions)</p>
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
<b>ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)</b>	
	<ul style="list-style-type: none"> <li>• Enhanced network accounting with up to the minute data on how the system is being used</li> <li>• Comprehensive management and enterprise scale tracking and reporting of print usage</li> <li>• Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>• Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>• Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>• Accept Authentication Login at control panel and pass to third party NetworkingAccount</li> <li>• Interface with third party accounting terminal for accounting user interface</li> </ul>
PAPER HANDLING	
<b>BYPASS TRAY</b>	
<b>Capacity<sup>5</sup></b>	150 sheets
<b>Sizes</b>	Custom sizes: 3 x 5 in. to 8.5 x 14 in. / 76 x 127 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Media Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Envelopes Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
<b>TRAY 1</b>	
<b>Capacity<sup>5</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm

Xerox® VersaLink® B610 Printer

<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
<b>UP TO 4 ADDITIONAL TRAYS</b>	
<b>Capacity<sup>5</sup></b>	550 sheets
<b>Sizes</b>	Custom sizes: 3 x 7.5 in. to 8.5 x 14 in./76.2 x 190 mm to 216 x 356 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover / 60 to 220 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Media Types</b>	Pre-Printed Recycled Envelopes (Tray 1 only) Labels Lightweight Cardstock Cardstock Letterhead Custom 1 - 5
<b>HIGH CAPACITY FEEDER (CAN BE COMBINED WITH UP TO 1 ADDITIONAL TRAY)</b>	
<b>Capacity<sup>5</sup></b>	2,000 sheets
<b>Sizes</b>	Standard sizes: A4 SEF, Letter SEF
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 65 lb. cover / 60 to 176 gsm 16 lb. bond to 65 lb. cover / 60 to 176 gsm
<b>Types</b>	Plain Paper Bond Punched Pre-Printed Recycled Lightweight Cardstock Letterhead Custom 1 - 5
<b>TOTAL PAPER CAPACITY<sup>5</sup></b>	
<b>Base Unit</b>	700 sheets
<b>Base Unit with Additional 550-sheet Tray</b>	1,250 sheets
<b>Base Unit with High Capacity Feeder</b>	2,700 sheets
<b>Base Unit with High Capacity Feeder and Finisher</b>	2,700 sheets
<b>Base Unit with High Capacity Feeder and Mailbox</b>	2,700 sheets
<b>Maximum Paper Capacity</b>	3,250 sheets

PAPER OUTPUT	
<b>OUTPUT TRAY</b>	
<b>Capacity<sup>5</sup></b>	500 sheets with tray full sensor (without Finisher or Mailbox)
<b>Automatic Two-sided Printing</b>	Standard
<b>FINISHER</b>	
<b>Capacity<sup>5</sup></b>	500-sheet tray, 50-sheet stapling
<b>MAILBOX</b>	
<b>Capacity<sup>5</sup></b>	Four 100-sheet bins
DEVICE MANAGEMENT	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour® / AirPrint® Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>REMOTE CONTROL PANEL</b>	
	<ul style="list-style-type: none"> <li>• Enables faster, more convenient technical support and user training</li> <li>• IT administrators and other authorized users can control the device remotely from a web page on any PC</li> <li>• Remote user experience is identical to performing tasks directly at the device</li> </ul>
<b>XEROX® CENTREWARE® WEB</b>	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray Status / Contents</li> <li>• Consumables Status</li> <li>• Billing / Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management — view and delete
<b>Job Submission</b>	Print-ready files (PS, PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>REMOTE SERVICES</b>	
<b>Automated Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Xerox® Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.



WHAT COMES IN THE BOX		
	VersaLink B600 Printer Standard Capacity Print Cartridge –Black: 10,300 print capacity <sup>6</sup> Software and Documentation CD (with User Manual, Quick Install Guide, Safety, Regulatory, Recycling and Disposal Guides, Print Drivers, and Warranty Statement) Installation Guide Quick Use Guides Power Cord	
SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
Extra-High Capacity Toner Cartridge	Black: 46,700 standard pages <sup>6</sup>	106R03944
High Capacity Toner Cartridge	Black: 25,900 standard pages <sup>6</sup>	106R03942
Standard Capacity Toner Cartridge	Black: 10,300 standard pages <sup>6</sup>	106R03940
Drum Cartridge	Black: 60,000 pages <sup>7</sup>	101R00582
<b>ACCESSORIES / OPTIONS</b>		
2,000-sheet High Capacity Feeder (includes Caster Base)		097S04948
550-sheet Feeder		097S04949
Finisher (500 sheets, 50-sheet stapler)		097S04952
4-Bin Mailbox (100 sheets per bin)		097S04953
Caster Base		097S04954
Cabinet (includes stabilizers)		097S04994
Wireless Network Adapter (Wi-Fi Kit)		497K16750
Productivity Kit with 320 GB HDD		497K18360
RFID Card Reader Kit		497K18380

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Recommended average throughput is not a minimum, but is intended to cover a range of volumes for different environments.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Paper capacities are based on 20 lb. / 75 gsm stock; capacities will vary with different weight stocks.

<sup>6</sup> Average standard pages. Declared Yield in accordance with ISO/IEC19752. Yield will vary based on image, area coverage and print mode.

<sup>7</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed. For more information visit: <https://www.office.xerox.com/latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling program.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.

